



Signature Colors® Granite Crystals



Product Description

Valspar Signature Colors Granite Crystals will add the glittering shine of rocks and minerals to your finish. Add Granite Crystals to Valspar Signature Colors Granite Paint for a shimmering, textured granite finish. Or, mix the Granite Crystals into Valspar Signature Colors Paint for sparkling glints of light.

Features

- Add sparkle to Granite Texture Paint
- Also for Signature Colors Paint

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: 1 oz. package – 6 per pack

Typical Properties (33888)

Vehicle Type: N/A

Sheen: N/A

Solids by Volume: N/A

Solids by Weight: N/A

Weight per Gallon: N/A.

VOC: Less than 50 g/L

Viscosity: N/A

Dry Time: N/A

Surface Coverage: N/A

Storage and Disposal

- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the Lead Warning in Cautions section.

Application and Clean-up

Use a stir stick to slowly stir Granite Crystals into paint with a circular stirring motion, lifting as you stir. Avoid pouring all the Granite Crystals in at once in order to assure that it is thoroughly mixed. Apply paint following label instructions. The Granite Crystals may not appear while applying the wet paint, but will show when finish is dry. **Note:** Granite Crystals may settle and become coated if paint is not used within 5 days of mixing. If more than 5 days have elapsed, you must add more Granite Crystals (This product is specifically formulated for Valspar Signature Colors Granite texture finish and paints). **Tip:** You may add more or less Granite Crystals to your finish as desired. One package per gallon will add subtle glimmering highlights in medium to dark colors. Two packages per gallon will show more highlights in lighter colors.

Cautions (33888)

WARNING: CONTAINS CRYSTALLINE SILICA. May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly-fitted respirator (NIOSH approved) during and after application. Avoid exposure to sanding dust by wearing an appropriate particulate respirator (NIOSH approved) during application, sanding and clean-up. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

Warning: This product contains chemicals known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long term exposure: Cancer Hazard. Crystalline silica may cause lung damage and cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 50 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.