



House & Trim Exterior Latex Primer



Product Description

Valspar® Exterior Latex Primer is the ideal prime coat under all oil and latex house paints. It is formulated with 100% acrylic resin for excellent adhesion, long-lasting protection and resistance to peeling and blistering. Blocks tannin stains on redwood and cedar and gives a mildew resistant coating.

Features

- Superior Adhesion
- Seals Surface
- Extends Life of Topcoat
- Gives Mildew Resistant Coating

Recommended Uses

- Bare wood
- Wood siding and trim
- Brick
- Concrete
- Cement
- Stucco
- Non-rusted galvanized gutters & downspouts

Colors and Base Information

	oz./gal.
Tintable White	128

Tinting: To enhance the appearance of the finish coat or hide wallpaper seams, tint the primer with Universal Tinting Colorants to a shade similar to the finish coat. Do not use more than 4 oz. of tinting color per gallon.

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Gallon & Quart – 4 per carton
5-gallon pail

Typical Properties (165219 Tintable White)

Vehicle Type: Acrylic Resin

Sheen: 0 – 10 Units @ 60° angle

Solids by Volume: 38%

Solids by Weight: 53%

Weight per Gallon: 11.0 lbs./gal.

VOC: Less than 50 g/L

Viscosity: 96 – 102 Kneb Units

Dry Time: 77°F (25°C) @ 50% Relative Humidity

To the touch: 30 minutes

Recoat: 2 hours for latex topcoats
Overnight for oil topcoats

Surface Coverage:

Up to 400 sq. ft. (37.2 m²)/gal. depending on surface porosity

At: 4 mil Wet, 1.5 mil Dry

Storage and Disposal

- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the Lead Warning in Cautions section. Clean and dry surface thoroughly, removing all dirt, dust, rust and grease.

Surface Preparation

Bare Wood: Remove sap and clean knotty areas. Then seal these areas by spot priming with an oil-based stain blocking primer/sealer.

Previously Painted Surfaces: Scrape loose and peeling paint, sand, then prime. Wire brush chalking areas and clean with TSP (or equivalent) and water removing as much chalk as possible. Dull glossy surfaces with gloss remover or sandpaper. Countersink nails and apply a rust inhibitive metal primer on exposed nail heads. Fill nail holes with putty. Caulk all cracks and joints.

Masonry: Brush loose sand, dust and other material from the surface.

Metal: May be used to prime weathered, non-rusted galvanized gutters and downspouts. New galvanized surfaces should be primed with a galvanized metal primer, or washed with a mild muriatic acid solution, or allowed to weather for 6 months before painting. All iron and steel surfaces should be primed with a rust inhibitive metal primer.

Application and Clean-up

Stir thoroughly before and occasionally during use. Apply only when air and surface temperatures are between 50 – 90°F (10 – 32°C). Thin only for spray application with up to 8 oz. of water per gallon. Apply with a premium quality polyester brush, “one coat” roller or airless sprayer. If applied by sprayer, back-roll or back-brush to work primer into the surface. Apply a liberal coat of primer uniformly, working well into the surface. Clean-up with warm, soapy water.

Cautions (165219 Tintable White)

WARNING: CONTAINS CRYSTALLINE SILICA. May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer’s directions for respirator use. AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use. Close container after each use.

WARNING: This product contains a chemical known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long-term exposure: Cancer Hazard. Contains crystalline silica which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 50 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.