

valspar

Multi-Purpose Interior/Exterior Latex Primer



Product Description

Valspar® Interior/Exterior Primer is a fast dry, low odor white pigmented primer/sealer. It's great for blocking a variety of stains including light water spots, graffiti, lipstick, crayon, grease, rust streaks, asphalt, pencil, smoke damage, surface burns, tannin bleed and mildew stains.

Features

- Adheres to Glossy Surfaces Without Sanding
- Blocks Stains
- Fast Drying
- Low Odor

Recommended Uses

- Wood
- Plaster
- Drywall
- Patching Compound
- Tape Joints
- Masonry
- Brick
- Plywood
- Ceiling Tiles

Colors and Base Information

	oz./gal.
Tintable White	128

Tinting: To assist in dramatic wall color changes, tint with up to 2 oz. per gallon of Universal Tinting Colorants to a shade similar to desired topcoat.

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Gallon & Quart – 4 per carton
5-gallon pail

Typical Properties (168215 Tintable White)

Vehicle Type: Acrylic Resin

Sheen: 30 – 40 Units @ 60° angle

Solids by Volume: 40%

Solids by Weight: 51%

Weight per Gallon: 10.4 lbs./gal.

VOC: Less than 100 g/L

Viscosity: 93 – 101 Krebs Units

Dry Time: 77°F (25°C) @ 50% Relative Humidity

To the touch: 15 – 30 minutes

Recoat: 1 hour for latex topcoat
4 hours for oil topcoat

Surface Coverage:

Up to 400 sq. ft. (37.2 m²)/gal. depending on surface porosity

At: 4 mil Wet, 1.6 mil Dry

Storage and Disposal

- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the Lead Warning in Cautions section. Clean and dry surface thoroughly. Scrub stained areas with an all-purpose cleaner to remove any residual stains. Remove all surface dirt, chalk, peeling paint and mildew.

Surface Preparation

Stains: Most stains can be sealed in one coat; however, stubborn stains may require additional coats. Always test first in a small hidden area to determine actual sealing results. Spot priming stubborn stains may be required.

Mildew Stains: This product seals residual mildew stains, but will not resist active mildew growth. Active mildew must be removed prior to application by scrubbing area with a commercial mildew remover or a mix of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Wear protective goggles and rubber gloves to avoid chemical contact with skin or eyes.

Previously Painted Surfaces: Normally, glossy surfaces would need to be dulled with a chemical deglosser or sanding; however, this product bonds to glossy surfaces with no sanding required.

New Wood Surfaces: Spot prime wood knots and areas of tannin bleed-through, once dry prime entire surface.

Metal: This product is not for use over metal but can be used over painted metal to seal light rust stains.

Application and Clean-up

Stir thoroughly before and occasionally during use. Apply only when air and surface temperatures are between 50 – 90°F (10 – 32°C). Thin only for spray application with up to 8 oz. water per gallon of paint. Apply with a premium quality polyester brush, “one coat” roller or airless sprayer. If applied by sprayer, back-roll or back-brush to work primer into the surface. Apply a liberal coat of primer uniformly, working well into the surface. Clean-up with warm, soapy water.

Cautions (168215 Tintable White)

WARNING: CONTAINS CRYSTALLINE SILICA. May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits wear an appropriate, properly-fitted respirator (NIOSH-approved) during and after application. Follow respirator manufacturer’s directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

WARNING: This product contains chemicals known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long-term exposure: Cancer Hazard. Contains crystalline silica which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732

This product contains less than 100 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.