

PDS #1015
PRODUCT INFORMATION

1191 Wheeling Road, Wheeling, IL 60090
 Phone: 847-541-9000 Fax: 847-541-7549



PRODUCT: 220489

DESCRIPTION:

Valspar® Signature Colors® Tuscan Accents

FEATURES:

Tuscan Accents is the second step of a two-step process. Use over Signature Colors Tuscan Accents Base Coat to create a two-color finish resembling antique Italian finishes in its unmistakable warmth and character. Bringing to mind old-world charm, it will add a sense of history to your home's décor.

WHERE TO USE:

Use on properly prepared wallboard, plaster, wood, masonry and brick.

SURFACE PREPARATION:

Tuscan Accents must be applied over Tuscan Accents Base Coat. Do not use other base coats. Follow Surface Preparation directions on Base Coat label.

APPLICATION:

Apply Signature Colors Tuscan Accents Base Coat and allow to dry for 24 hours. Do not use a substitute base coat.

Brush Application: Apply Tuscan Accents with the Color Washing Brush. Dip the brush 1-2" into the paint. Using both sides of the brush, apply in small crisscross "X" patterns. Work in 3' X 3' sections using random strokes filling in all white space within each section. In the same 3' X 3' section, without reloading the brush, blend the "X" pattern brush strokes. Use long, sweeping motions going both vertical and horizontal to blend. Repeat these steps in each section until the wall is complete.

Smoothing: Wait 10 minutes or until the colored portion of the paint has started to lose the "wet-look". The contrasting white particles will appear to be raised on the surface. Use the Tuscan Smoother to "open-up" the white particles. Holding the Smoother at a 30-degree angle to the surface and using a light touch, stroke the surface with sweeping motions, similar to the blending step above. Use both sides of the Smoother and vary the direction of each stroke to create a unique effect. If scratches or streaks occur, you may be attempting to smooth too soon or are pressing too hard. Remove paint accumulation from the Smoother to avoid scratching the wet surface. To correct any gaps in color or other mistakes, fill in those places with small amounts of Tuscan Accents. Then blend and smooth as before.

Note: Use of the Smoother is optional if smaller white particles are desired. If walls have a texture, the Smoother should not be used.

220489 Valspar Signature Colors Tuscan Accents

TYPICAL PRODUCT PROPERTIES:

VEHICLE TYPE:	Latex Emulsion
VOC:	100 g/l max
WT/GAL:	11 lbs.
VISCOSITY:	Thick Paste
FLASHPOINT:	N/A
60° GLOSS:	10-20 Units

COVERAGE:

One gallon covers approximately 400 sq. ft. (37.2 m²) depending on surface porosity and texture. Do not thin.

FILM THICKNESS: 4.0 Mil Wet

DRY TIMES:

Apply only when surface and air temperatures are 50-90°F (10-32°C). Dries to the touch in 1-3 hours.

THINNING/CLEAN UP:

Do not thin. Clean tools and hands with warm, soapy water.

PACKAGING:

Gallons 4 Pack

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Product Information Hotline:

1-888-313-5569

CAUTIONS:

May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

This product contains less than 100 g/L VOC (0.8 lb./Gal VOS)

TYPICAL ANALYSIS

CAS NO.	INGREDIENTS
7732-18-5	Water
Not Avail.	Latex Emulsion
7631-86-9	Amorphous Silica

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.