



Medallion® Exterior Flat House Paint



Product Description

This tough, 100% acrylic house paint keeps your home safe from the weather. The low gloss flat flows on easily for a smooth, even finish. Dries quickly and cleans up easily with soap and water. Gives mildew resistant coating.

Features

- Finest Quality
- 100% Acrylic Latex
- One Coat Coverage
- Ultimate Durability
- Smooth Finish
- Gives Mildew Resistant Coating

Recommended Uses

- Wood siding and trim
- Hardboard siding
- Primer metal
- Shakes & shingles
- Brick, cement, cinder block & concrete
- Stucco
- Stone
- Asbestos
- Galvanized steel, aluminum & vinyl siding

Colors and Base Information

	oz./gal.
White	128
Tint Base	124
Clear Base	116
Pastel Base	126

Reference store Database for available colors.

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Quart & Gallon – 4 per carton
5-gallon pail

Typical Properties (45501 Series)

Vehicle Type: Acrylic Resin

Sheen: 0–6 Units @ 85° angle

Solids by Volume: 36%

Solids by Weight: 54%

Weight per Gallon: 11.7 lbs./gal.

VOC: Less than 50 g/L

Viscosity: 94–100 Krebs Units

Dry Time: 77°F @ 50% Relative Humidity

To the touch: 30 minute(s)

Recoat: 4 hour(s)

Washing: Allow at least 7 days before washing. Use mild detergent and sponge.

Full Cure: 1 day(s)

Surface Coverage:

400 sq. ft./gal.

At: 4.0 mil Wet, 1.4 mil Dry

Storage and Disposal

- Do not freeze.
- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the Lead Warning in Cautions section. Clean and dry the surface thoroughly, removing all dirt, dust, rust and grease. On bare wood, coat knots and sappy areas with satin block primer/sealer. Then prime entire surface with exterior oil or latex primer. On previously painted surfaces, scrape, sand, then prime. Wire brush badly chalking areas. Dull glossy surfaces with gloss remover or sandpaper. Countersink nails and fill with putty. Caulk all cracks and joints. On unprimed, preprimed or previously painted hardboard siding, primer with an exterior oil primer. On masonry, wire brush loose materials from chalky areas. On metal, remove rust on galvanized gutters and prime with a rust inhibitive primer. On new galvanized surfaces, remove rust, clean with mineral spirits and prime with a rust inhibitive primer. On vinyl siding, wash weathered vinyl siding thoroughly and allow to dry. Then paint with a color lighter than the original siding color. **WARNING!** Painting vinyl siding with darker colors will cause warping or deformation from heat absorption. **CLEAN MILDEW FROM THE SURFACE!** Mildew is a fungus that looks like dirt, but won't wash off. Mildew must be removed before painting or it will grow through any new coating. To remove mildew, scrub with a commercial mildew remover or a solution of 1 part liquid bleach to 3 parts water. Rinse thoroughly and allow to dry. Protect eyes and skin by wearing protective equipment, including rubber gloves and eye goggles while working with the bleach solution.

Application and Clean-up

Paint only when surface and air temperatures are 50–90 °F (10–32 °C). Stir paint thoroughly before and occasionally during use. Use a premium quality roller or polyester brush or airless sprayer following manufacturer's directions. Paint the gutters, window sashes and frames first, then start at the top of the house and work from right to left using crisscross strokes. Always end up at a door, window or outer edge. **Thinning/Clean Up:** Thin only for spray application with up to 8 oz. water per gallon of paint. Clean up with warm water.

Cautions (45501 Series)

WARNING: CONTAINS CRYSTALLINE SILICA. May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly-fitted respirator (NIOSH approved) during and after application. Avoid exposure to sanding dust by wearing an appropriate particulate respirator (NIOSH approved) during application, sanding and clean-up. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

Warning: This product contains chemicals known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long term exposure: Cancer Hazard. Contains crystalline silica which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 50 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.