

**PDS #1025
PRODUCT INFORMATION**

1191 Wheeling Road, Wheeling, IL 60090
Phone: 847-541-9000 Fax: 847-541-7549



272424 Valspar Signature Colors Brushed Pearl

PRODUCT: 272424

DESCRIPTION:

Valspar® Signature Colors® Brushed Pearl

FEATURES:

Impart a dimensional iridescent finish to walls with Valspar Signature Colors Brushed Pearl Glaze. This faux finish is subtle, incorporating gentle tones for a muted effect. It's simple to apply, and will add elegance and sophistication to any room.

WHERE TO USE:

Use on properly prepared wall and ceiling surfaces.

SURFACE PREPARATION:

Surface should be clean and dry. Scrape off loose paint and patch all holes, cracks and indentations. Any imperfections and wall seams will be more visually apparent with a metallic paint.

APPLICATION:

Apply a base coat of Valspar® Signature Colors® Interior Satin Wall and Trim Paint in a color similar to your chosen Brushed Pearl Glaze. Allow to dry completely.

Use color wash brush to apply Brushed Pearl, cut in along ceiling, floor and molding of a 4' x 8' working area and then proceed to the main wall brushing in "x" patterns. Apply an even, opaque layer. Thicker applications can be smoothed out with the trowel. Return to beginning of working area. Hold the plastic float trowel and press into the wet surface and move the material in a circular motion. The trowel should grab slightly and create a swirl effect. If the surface is too wet it will "slip" over the material and it is necessary to wait a little longer before using the trowel. Clean trowel if dry product builds up. Continue across the wall applying Brushed Pearl and swirling with the plastic float trowel. Allow the surface to dry for four hours. Apply a second coat of Brushed Pearl if desired using the same method.

Note: Brushed Pearl has a set up time that's necessary to create the swirl or cloud like appearance with the plastic float trowel. The trowel will grab slightly when the proper set up time occurs. Thickness of application and environmental conditions will greatly affect or determine set up time. In higher humidity or cooler temperatures, it is possible to brush out an entire wall up to an 8' x 10' area and work back into it with the plastic float trowel. In dryer conditions, it will be necessary to work in puzzle piece sections measuring approximately 4' x 4'.

Protecting the Finish: Surfaces exposed to frequent washing and moisture should be protected with Valspar® Signature Colors® Faux Clear Protector. Follow all label instructions.

TYPICAL PRODUCT PROPERTIES:

VEHICLE TYPE: Acrylic Polymer
VOC: 350 g/l max
WT/GAL: 11 lbs.
VISCOSITY: Thick Paste
FLASHPOINT: N/A
60° GLOSS: 10-20 Units

COVERAGE:

One gallon covers approximately 100-200 sq. ft. (9.3-18.6m²) depending on surface porosity and texture. Do not thin.

FILM THICKNESS: 4.0 Mil Wet

DRYING TIME:

Apply only when surface and air temperatures are 50-90°F (10-32°C). Dries to the touch in 1-3 hours. Wait 4 hours before applying second coat.

THINNING/CLEAN-UP:

Do not thin. Clean up with warm, soapy water.

PACKAGING:

Gallons - 4 Pack

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal.

Product Information Hotline:

1-888-313-5569

CAUTIONS:

May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

This product contains less than 350 g/L VOC (2.9 lb./Gal VOS)

TYPICAL ANALYSIS

CAS NO.	INGREDIENTS
7732-18-5	Water
Not Avail.	Acrylic Polymer
12001-26-2	Mica
14807-96-6	Talc
57-55-6	Propylene Glycol
112-27-6	Triethylene Glycol

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.