



Contractor Primers Interior PVA Primer



Product Description

Valspar® PVA Primer is specially formulated for the needs of the Pro painter. Our PVA primer effectively seals porous surfaces preparing them for any architectural topcoat. Valspar PVA Primer can be used over bare or previously painted drywall, plaster, wood, and masonry. Due to its great flow and leveling properties Valspar PVA primer can be brushed, rolled, or sprayed with ease.

Features

- Seals Unpainted Drywall & Plaster
- Provides Uniform Surface
- For Use with Latex and Oil-based Paints

Recommended Uses

- Drywall
- Plaster
- Wood
- Brick
- Cement
- Masonry
- For Interior Use Only

Colors and Base Information

	oz./gal.
White	128

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Gallon – 4 per carton
5-gallon pail

Typical Properties (305011)

Vehicle Type: Vinyl Acrylic

Sheen: 20 – 30 Units @ 85° angle

Solids by Volume: 24%

Solids by Weight: 40%

Weight per Gallon: 10.5 lbs./gal.

VOC: Less than 50 g/L

Viscosity: 95 – 105 Krebs Units

Dry Time: 77°F (25°C) @ 50% Relative Humidity

To the touch: 30 minutes

Recoat: 3 – 4 hours

Washing: Allow at least 7 days before washing. Use mild detergent and sponge.

Surface Coverage:

Smooth Surface: 400 – 500 sq. ft./gal.

Rough: 250 – 350 sq. ft./gal.

At: 4 mil Wet, 1.6 mil Dry

Storage and Disposal

- Do not freeze.
- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the Lead Warning in Cautions section. Clean and dry surface thoroughly, removing all dirt, dust, rust, grease and wax. Scrape off loose or peeling paint. Remove glue, shellac and sizing. Patch cracks and spot-prime. Dull glossy surfaces with gloss remover or sandpaper.

Surface Preparation

New Drywall/Wallboard: Tape joints should be sanded smooth and even with the drywall or wallboard. Using a damp cloth or sponge, wipe tape joints and all wallboard surfaces to remove all sanding dust. Be sure to remove all chalky residue before priming. Allow to dry, then prime.

Plaster: Must be dry, fully cured and in good condition. Remove chalky residue.

Concrete/Masonry: Must be dry, fully cured and in good condition. Remove all chalk and efflorescence. Fill the pores of concrete block with a latex block filler. Soft concrete or masonry surfaces should be primed with a masonry block filler.

Application and Clean-up

Use a paint paddle or mixing blade to stir primer thoroughly. Apply only when primer, surface and air temperatures are 50 – 90°F (10 – 32°C) during application and drying time. For airless spray, thin with up to 8 oz. water per gallon, only if paint is too thick for sprayer.

Brush – Use premium quality polyester brush.

Roller – Use a premium quality polyester roller with 1/2 to 3/4 inch nap.

Airless Spray – Use 2000 PSI with a 0.015 to 0.021 tip.

Clean-up with warm, soapy water.

Cautions (305011)

WARNING: CONTAINS CRYSTALLINE SILICA. May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits wear an appropriate, properly-fitted respirator (NIOSH-approved) during and after application. Follow respirator manufacturer's directions for respirator use. AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use. Close container after each use.

WARNING: This product contains chemicals known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long-term exposure: Cancer Hazard. Contains crystalline silica which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 50 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.