



Ultra Premium Interior Latex Satin Series



Product Description

Valspar® Ultra Premium Satin Finish low gloss sheen will accent every room in your home with just one coat. This stain resistant and scrubbable finish will maintain its fresh appearance and is guaranteed to last a lifetime.

Features

- Long Lasting Durability
- Thick, One Coat Coverage
- Stain Resistant & Scrubbable
- Soap & Water Clean-Up
- Low Odor
- 100% Acrylic Latex
- Gives Mildew Resistant Finish

Recommended Uses

- Plaster
- Wood
- Brick
- Drywall
- Cement
- Metal

Colors and Base Information

	oz./gal.
Ready Mix*	128
Base 1	126
Base 2	124
Base 4	116

Reference Lowe's store database for available colors.

*Antique White

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Quart, Gallon – 4 per carton
5-gallon pail

Typical Properties (40233 White)

Vehicle Type: Acrylic Resin

Sheen: 22 – 32 Units @ 85° angle

Solids by Volume: 36%

Solids by Weight: 49%

Weight per Gallon: 10.9 lbs./gal.

VOC: Less than 50 g/L

Viscosity: 97 – 103 Kreb Units

Dry Time: 77°F @ 50% Relative Humidity

To the touch: 30 – 60 minutes

Recoat: 2 – 4 hours

Washing: Wait at least 7 days before washing with a mild detergent and soft sponge.

Surface Coverage:

Up to 400 sq. ft./gal. depending upon surface porosity.

At: 4.0 mil Wet, 1.5 mil Dry

Storage and Disposal

- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the lead warning in Cautions section. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Patch cracks and spot prime. Dull glossy surfaces. Prime new wallboard with latex wall primer. Prime new wood with enamel undercoater or latex wall primer.

Application and Clean-up

Stir paint thoroughly. Intermix all containers to ensure uniform color. Paint only when surface and air temperatures are 50 – 90°F (10 – 32°C) during application and drying time. Thin only for spraying with up to 8 oz. of water per gallon of paint. Apply with a premium quality roller, polyester brush or airless sprayer. Paint the ceiling first, then the walls. If applying by roller, roll from dry area into wet using firm, crisscross strokes. Finish with long, even strokes in one direction. Clean tools and hands with warm, soapy water.

Cautions (40233 White)

WARNING: May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly-fitted respirator (NIOSH-approved) during and after application. Follow respirator manufacturer's directions for respirator use. AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use. Close container after each use.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** IF SWALLOWED: Drink 2 glasses of water. **Get medical attention immediately.**

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.**
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 50 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.

valspar

1191 Wheeling Rd, Wheeling, IL 60090 888-313-5569
www.valspar.com

11/09

PDS 0130