



House & Trim Exterior Oil Primer



Product Description

Valspar® Exterior Oil Primer is the perfect base coat for all oil and latex house paints, adding long-lasting protection to your home as it resists weather-related problems such as peeling and blistering. Gives mildew resistant coating that helps promote topcoat adhesion as it seals and primes exterior surfaces.

Features

- Maximum Adhesion
- Blocks Stains
- Extends Life of Topcoat
- Gives Mildew Resistant Coating

Recommended Uses

- Hardboard siding and trim
- Wood siding and trim
- Bare redwood, cedar, cypress, fir or gummy pine

Colors and Base Information

	oz./gal.
Tintable White	128

Tinting: To enhance the appearance of the finish coat or hide wallpaper seams, tint the primer with Universal Tinting Colorants to a shade similar to the finish coat. Do not use more than 4 oz. of tinting color per gallon.

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Gallon & Quart – 4 per carton
5-gallon pail

Typical Properties (47428 Tintable White)

Vehicle Type: Alkyd Resin

Sheen: 0 – 10 Units @ 60° angle

Solids by Volume: 56%

Solids by Weight: 75%

Weight per Gallon: 11.5 lbs./gal.

VOC: Less than 350 g/L

Viscosity: 85 – 91 Kneb Units

Dry Time: 77°F (25°C) @ 50% Relative Humidity

To the touch: 6 – 8 hours

Recoat: Dry overnight before topcoat

Apply finish coat within 30 days

Surface Coverage:

Up to 400 sq. ft. (37.2 m²)/gal. depending on surface porosity

At: 4 mil Wet, 2.3 mil Dry

Flashpoint: 119°F

Storage and Disposal

- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.
- **Danger:** Rags, steel wool, sanding dust or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool, sanding dust or waste in a sealed, water-filled metal container.

Surface Preparation

Read the Lead Warning in Cautions section. Clean and dry surface thoroughly, removing all dirt, dust, rust and grease.

Surface Preparation

Bare Wood: Spot prime knots and sappy areas with Valspar Interior Oil Multi-Purpose Primer after removing sap by scraping and cleaning with mineral spirits. Then, prime the entire surface with this product.

Hardboard Siding: Remove any wax from bleed-through areas by wiping with a mineral spirits soaked cloth, turning the cloth often.

Previously Painted Surfaces: Scrape, sand, then prime. Wire brush badly chalking areas and wash with TSP and water. Dull glossy surfaces with gloss remover or sandpaper. Countersink nails, fill with putty. Apply a rust inhibitive metal primer on exposed nails. Caulk all cracks and joints.

Metal: Remove rust and apply a rust inhibitive metal primer.

Application and Clean-up

Stir thoroughly before and occasionally during use. Apply only when air and surface temperatures are between 50 – 90°F (10 – 32°C). Do not thin. Apply with a premium quality polyester brush, “one coat” roller or airless sprayer. If applied by sprayer, back-roll or back-brush to work primer into the surface. Apply a liberal coat of primer uniformly, working well into the surface. Clean-up with mineral spirits.

Cautions (47428 Tintable White)

WARNING: CONTAINS PETROLEUM DISTILLATE AND CRYSTALLINE SILICA. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. USE ONLY WITH ADEQUATE VENTILATION. Keep away from heat, sparks and flame. Avoid breathing vapors, spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness or if air monitoring demonstrates vapor/mist levels above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer’s directions for respirator use. AVOID CONTACT WITH THE EYES AND SKIN. Wash thoroughly after use. Close container after each use.

WARNING: This product contains a chemical known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Do not induce vomiting. **Get medical attention immediately.**

Delayed effect from long-term exposure: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. Cancer Hazard. Crystalline silica can cause lung damage and cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.**
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 350 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.

PDS 0777

valspar

1191 Wheeling Rd, Wheeling, IL 60090 888-313-5569
www.valspar.com

03/09