

PDS #5722
PRODUCT INFORMATION

valspar

1191 Wheeling Road, Wheeling, IL 60090
Phone: 847-541-9000 Fax: 847-541-7549



48935 Valspar Interior Ltx Primer Bare Wood Undercoat

PRODUCT: 48935

DESCRIPTION:

Valspar Interior Latex Primer Bare Wood Undercoat

FEATURES:

This primer is a water-base, sandable primer intended for use on interior bare wood under latex or oil base enamel topcoats. It seals porous wood surfaces and sands to a smooth base to maximize topcoat gloss uniformity.

WHERE TO USE:

Use on properly prepared interior wood and wall surfaces including woodwork, trim, walls, ceilings, drywall and plaster. Do not use on bare metal or over glazed, glossy surfaces.

SURFACE PREPARATION:

General: Clean and dry surface thoroughly, removing all dirt, dust, rust, grease and wax.

New Wood Surfaces: Sand smooth before priming. Remove chalky residue from unpainted wallboard and plaster.

Previously Painted Surfaces: Scrape off loose paint and wallpaper. Remove glue, shellac and sizing. Plaster cracks and spot prime. Dull glossy surfaces with gloss remover or sandpaper.

TYPICAL PRODUCT PROPERTIES:
(48935 White)

VEHICLE TYPE: Vinyl Acetate Ethylene Copolymer
SOLIDS: 50% WT. 33% VOL.
VOC: 200 g/l max
WT/GAL: 11.2 lbs.
VISCOSITY: 82-90 KU
FLASHPOINT: N/A
60° GLOSS: 0-8 Units

COVERAGE / THINNING:

One quart covers up to 100 sq. ft. (9.3 m²) depending on surface porosity. Do not thin.

FILM THICKNESS: 4.0 mil Wet
1.2 mil Dry

DRY TIMES:

Apply only when surface and air temperatures are between 50-90°F (10-32°C). Allow to dry 2 hours before sanding or applying finish coats.

APPLICATION:

Stir thoroughly before and during use. Apply with a premium quality polyester brush or roller. Apply a liberal coat of primer uniformly, working well into the surface. When dry, sand lightly with fine sandpaper to a smooth surface and remove all sanding dust. Allow to dry at least 2 hours before applying a latex topcoat, 4 hours for oil topcoat.

TINTING:

Do not use more than 1 oz. (29 ml) of tinting color per quart.

CLEAN UP:

Clean up with warm, soapy water.

PACKAGING:

Quarts 4 Pack

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Product Information Hotline:

1-888-313-5569

TYPICAL ANALYSIS: (48935 White)

C.A.S. NO.	INGREDIENTS
7732-18-5	Water
1317-65-3	Calcium Carbonate
Unknown	Vinyl Acetate Ethylene Copolymer
13463-67-7	Titanium Dioxide
107-21-1	Ethylene Glycol
14808-60-7	Crystalline Silica

CAUTIONS:

CONTAINS CRYSTALLINE SILICA

May cause eye and skin irritation. Avoid breathing spray mist dust or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

WARNING: This product contains a chemical known to the State of California to cause cancer.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long-term exposure: Cancer Hazard. Contains crystalline silica which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.
EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

**This product contains less than
200 g/L VOC (1.7 lb./Gal VOS)**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.