



## Signature Colors® Interior Latex Satin Series



### Product Description

Valspar® Signature Colors® offers the colors of leading designers and most popular brands in a revolutionary paint finish. It is a paint and primer in one product that makes application simple and easy. This innovative paint technology, Duramax Ti3 includes the highest quality 100% acrylic resins to deliver superior color definition and superior durability. This stain resistant finish can be washed, even scrubbed and it will retain its like-new appearance. Enhance bedrooms, dens and hallways with this classic, low sheen finish.

### Features

- Designer Inspired Colors
- Our Thickest One-Coat Coverage
- Paint & Primer-in-One Product
- Stain Resistant & Scrubbable
- Gives Mildew Resistant Finish
- Smooth Application & Finish
- 100% Acrylic Latex
- Soap & Water Clean-Up
- Low Odor

### Recommended Uses

- Plaster
- Wood
- Brick
- Drywall
- Cement
- Metal

### Colors and Base Information

	oz./gal.
White	128
Base 1	126
Base 2	124
Base 4	116

Reference Lowe's store Database for available colors.

### Shipping and Packaging

**Freight Classification:** Paint or Paint Related Material. Protect from freezing.

**Packaging:** Quart, Gallon – 4 per carton

### Typical Properties (72476 Base 1)

**Vehicle Type:** Acrylic Resin

**Sheen:** 10 – 18 Units @ 85° angle

**Solids by Volume:** 36%

**Solids by Weight:** 52%

**Weight per Gallon:** 11.1 lbs./gal.

**VOC:** Less than 50 g/L

**Viscosity:** 103 – 110 Krebs Units

**Dry Time:** 77°F @ 50% Relative Humidity

**To the touch:** 30 – 60 minutes

**Recoat:** 2 – 4 hours

**Full Cure:** 30 days

**Surface Coverage:**

Up to 400 sq. ft./gal. (37.2 m<sup>2</sup>) depending on surface porosity.

**At:** 4 mil Wet, 1.5 mil Dry

### Storage and Disposal

- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

## Surface Preparation

Read the lead warning in Cautions section. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Dull glossy surfaces. Patch cracks and spot-prime. Signature Colors paint can be used to prime patched areas and bare surfaces before applying the finish coat. For best results on heavily stained areas, use a coat of Valspar® Multi-Purpose Latex Primer. For drastic color changes or deep, vivid colors, prime with Valspar® Tintable Primer for optimal color accuracy and coverage.

## Application and Clean-up

Stir paint thoroughly. Intermix all containers to ensure uniform color. Paint only when surface and air temperatures are 50 – 90°F (10 – 32°C) during application and drying time. Do not thin. Apply with a premium quality roller, polyester brush or airless sprayer. Paint the ceiling first, then the walls. If applying by roller, roll from dry area into wet using firm, crisscross strokes. Finish with long, even strokes in one direction. Clean tools and hands with warm, soapy water.

## Cautions (72476 Base 1)

**WARNING: CONTAINS CRYSTALLINE SILICA.** May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH-approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after use.

**Warning:** This product contains chemicals known to the State of California to cause cancer.

**FIRST AID:** EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** IF SWALLOWED: Drink 2 glasses of water. **Get medical attention immediately.**

**Delayed effect from long term exposure:** Cancer Hazard. Contains crystalline silica, which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN.**  
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

This product contains less than 50 g/L VOC

PDS 0042

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.

valspar

1191 Wheeling Rd, Wheeling, IL 60090 888-313-5569  
[www.valspar.com](http://www.valspar.com)

09/09