



Duramax® Exterior Latex Flat Series



Product Description

Valspar® Duramax® is an ultra premium exterior paint representing the latest in coating innovation. Infused with Advanced Crosslinking Technology “ACT”, this self-priming finish provides triple resistance against mold, mildew and algae growth on the paint film, as well as providing maximum UV protection. The thicker finish hides minor surface defects and bridges small cracks for a flawless finish. Duramax with “ACT” ensures a lifetime of protection – guaranteed.

Features

- Advanced Technology
- 100% Acrylic Latex
- Our Thickest One Coat Coverage
- Self Priming
- UV Resistant
- Gives Mold, Mildew & Algae Resistant Coating

Recommended Uses

- Wood Siding & Trim
- Hardboard Siding; Fiber Cement Board
- Primed Metal
- Shakes; Asbestos Shingles
- Brick; Cement; Cinder Block
- Stucco; Concrete; Stone
- Aluminum & Vinyl Siding

Colors and Base Information

	oz./gal.
Base 1	126
Base 2	124
Base 4	116

Reference Lowe’s store Database for available colors.

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Gallon – 4 per carton
5-gallon pail

Typical Properties (73754 White)

Vehicle Type: Acrylic Resin

Sheen: 0 – 8 Units @ 60° angle

Solids by Volume: 40%

Solids by Weight: 58%

Weight per Gallon: 12.1 lbs./gal.

VOC: Less than 50 g/L

Viscosity: 95 – 100 Kneb Units

Dry Time: 77°F @ 50% Relative Humidity

To the touch: 1 hour

Recoat: 4 hours

Surface Coverage:

300 – 400 sq. ft./gal. (27.9 - 37.2 m²)
depending on surface porosity.

At: 4 mil Wet, 1.4 mil Dry

Storage and Disposal

- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the Lead Warning in Cautions section. Clean and dry surface thoroughly, removing all dirt, dust, chalk, rust, grease, wax and mildew. To remove mildew or suspected mildew, scrub house before painting with a commercial mildew remover or a solution of 1 part liquid chlorine bleach to 3 parts water. Rinse thoroughly. Avoid contact with skin or eyes.

PDS 0080

Surface Preparation

Previously Painted Surfaces (including painted metal siding): Scrape off loose and peeling paint, sand smooth. Thoroughly remove chalk by vigorous washing, then rinse. Dull glossy surfaces with gloss remover or sandpaper. Countersink nails and apply an oil metal primer to exposed nail heads. Caulk cracks and joints.

Bare Wood: For maximum performance, 2 coats of Duramax are recommended.

Vinyl Siding: Wash thoroughly and allow to dry. Then paint with a color lighter than original siding color. **WARNING** – Painting with darker colors will cause warping or deformation from heat absorption.

Masonry: Brush loose sand, dust and other material from the surface.

Metal: New galvanized surfaces should be allowed to age six months before painting.

Application and Clean-up

Stir paint well and intermix containers of the same color. Apply product at temperatures ranging from 35 – 90°F (2 – 32°C). Apply with a premium quality roller or polyester brush. Do not thin. Start at the highest point of the house and work across. Always paint back into freshly painted areas and end up at a door, window or outer edge. Move windows after one hour to prevent sticking. Clean up with warm, soapy water.

Cautions (73754 White)

WARNING: CONTAINS CRYSTALLINE SILICA. May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH-approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after use.

Warning: This product contains chemicals known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long term exposure: Cancer Hazard. Contains crystalline silica, which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 50 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.