

PDS #5188
PRODUCT INFORMATION

valspar

1191 Wheeling Road, Wheeling, IL 60090
Phone: 847-541-9000 Fax: 847-541-7549



95958 Valspar Ultra Premium Ceiling Texture Paint

PRODUCT: 95958

DESCRIPTION:

Valspar Ultra Premium Interior Latex Acrylic Ceiling Texture Paint

FEATURES:

Beautify your interior ceilings with Valspar Ultra Premium Ceiling Texture Paint. This premium quality paint provides ceilings with a dramatic “popcorn type” texture to hide minor surface imperfections.

WHERE TO USE:

Ideal for properly prepared plaster, drywall, acoustical tiles, wood, metal, cement, brick and masonry. Not recommended for walls. **DO NOT USE OVER WALLPAPER.**

SURFACE PREPARATION:

Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Patch cracks and spot prime. Dull glossy surfaces. Remove chalky residue and prime new wallboard with latex wall primer. New plaster and masonry must cure 30 days before priming. Prime bare wood with an acrylic enamel undercoater. Prime ferrous metal with a rust inhibiting oil metal primer. For other metals, use appropriate metal primer. Water stained ceilings or other stained areas must be primed with a latex or oil-base stain block primer to prevent bleed-through.

Note: Oil-based primers dry to a hard, slippery surface and must be roughened by sanding to increase texture paint adhesion.

TYPICAL PRODUCT PROPERTIES:
(95958 Ceiling Texture)

VEHICLE TYPE: Vinyl Acrylic
SOLIDS: 59% WT. 38% VOL.
VOC: 100 g/l max
WT/GAL: 12.9 lbs.
VISCOSITY: 141+ KU
FLASHPOINT: N/A
60° GLOSS: N/A

COVERAGE/THINNING:

One gallon covers approximately 50-60 sq. ft. (4.6-5.6 m²) depending upon texture pattern and surface porosity. A heavier stipple requires much more paint. Thin sparingly only if paint becomes too thick to apply.

FILM THICKNESS: 32 mil Wet
12 mil Dry

DRY TIMES:

Paint only when surface and air temperatures are 50-90°F (10-32°C). Dries hard overnight and cures fully in one week.

95958 Valspar Ultra Premium Ceiling Texture Paint

APPLICATION:

Mix well before and during use. Intermix all cans to ensure uniform color. Use a stiff brush, putty knife or trowel. Working in 3-foot squares, smooth out surface with a premium quality looped texture roller or a medium nap (1/2 - 3/4 inch) roller. Work new areas into the adjoining areas while both are still wet. Finish with long, even strokes, blending into finished areas.

CLEAN UP:

Clean up with warm, soapy water.

PACKAGING:

Gallons 4 Pack
2-Gallon Pail Each

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

**Product Information Hotline:
1-888-313-5569**

TYPICAL ANALYSIS (95958 Ceiling Texture)

| C.A.S. NO. | INGREDIENTS |
|------------|-------------------------|
| 7732-18-5 | Water |
| 1317-65-3 | Calcium Carbonate |
| 93763-70-3 | Amorphous Silica |
| 13463-67-7 | Titanium Dioxide |
| 25067-01-0 | Vinyl Acrylic Copolymer |
| 14808-60-7 | Crystalline Silica |

CAUTIONS:

CONTAINS CRYSTALLINE SILICA

May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use. Warning: This product contains a chemical known to the state of California to cause cancer.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.** **Delayed effect from long-term exposure:** Cancer Hazard. Contains crystalline silica which can cause cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

**This product contains less than
100 g/L VOC (0.8 lb./Gal VOS)**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.